

KEIM Putzgrund Render base coat



1. Product description

Keim Putzgrund is a mineral render base coat with a rough surface and good filling and covering properties.

2. Field of application

Keim Putzgrund is suitable for interior and exterior application. Keim Putzgrund is an undercoat for Keim Brillantputz for use on old and new render, internal plaster and plasterboard.

Keim Putzgrund reduces the absorbency of the underlying surface and increases the working time of Keim Brillantputz. The rough surface enables application of Keim Brillantputz on very smooth surfaces.

Also for use over previously painted surfaces prior to application of Keim Universal Render.

3. Product properties

Material characteristics

Density: 1.42g/cm³
Resistance to vapour diffusion: $s_d=0.02$ m

4. Application instructions

Substrate preparation

All loose, flaking and unstable material must be identified and then thoroughly removed, all surfaces must be thoroughly washed down with clean cold water to remove all surface dirt and dust. When all surfaces are clean, sound, wind dry, dust free and free from all surface contaminants, application of Keim Putzgrund may proceed.

Any newly rendered/repared areas must be allowed to harden for a minimum period of 14 days.

Application

Keim Putzgrund should be diluted with Keim Granital Dilution (max 10%) if required and should be evenly applied by brush or roller.

Application conditions

Ambient and substrate temperature above 5°C and below 30°C. Do not apply in direct sunlight or onto sun-heated surfaces, nor if it is raining or if there is an immediate likelihood of rain.

Consumption

Approximately 0.3 kg/m²

Cleaning of tools

Clean immediately after use with water

5. Packaging

25kg sacks

6. Storage

The product has a shelf life of 12 months if stored in a cool and frost-free place.

7. Disposal

EC Waste Code No. 08 01 12

Any residues must be emptied out of containers before recycling.

8. Safety instructions

Cover surfaces which are not to be painted, in particular glass, natural stone, ceramics etc. Protect the eyes and skin from splashes. Keep out of reach of children.



Refer to COSHH data sheet.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.



KEIM
MINERAL PAINTS LTD

Santok Building
Deer Park Way, Donnington Wood
Telford, Shropshire, TF2 7NA
Tel. (01952) 231250
Fax (01952) 231251

www.keimpaints.co.uk
sales@keimpaints.co.uk